

MATERIAL SAFETY DATA SHEET

I. IDENTIFICATION

n DEI(III IOIIIIOI)			
Manufacturer:	Harkness Industries	Telephone:	203-272-3219
	50 Grandview Court	_	
	Cheshire, CT. 06410		
Trade Name:	None	CAS Number:	NA
Chemical name:	Thermoset Polyurethane Elastomer	Chemical Family:	Polyurethane
	-	·	

II. SPECIAL REGULATORY HAZARDS

Ingredient	CAS No.	Exposure Limit	OSHA (1910.1200)	EEC*
Product	N/A	N/D	Not Hazardous	Not Hazardous
Transportation:	N/A			

Not Applicable: Polyurethane elastomers are fully reacted polymers molded into articles, which are not considered hazardous.

III. PHYSICAL DATA

Appearance and Odor:	Molded Parts or sheets,		
	no characteristic odor		
Solubility:	Insoluble in water	Specific Gravity (H 0=1):	1.1-1.25
Melting Point:	N/A	Vapor Pressure @ 20 C.	N/A
Boiling Point:	N/A	Vapor Density (Air=1):	N/A
Other Data:	None	Volatility @ 70 F:	None

IV. FIRE AND EXPLOSION HAZARD DATA

Flash Point:	N/A	Auto ignition Temp:	N/D
Extinguishing Media:	Water Spray, Dry Chemical, Foam, or	Flammable Limits in Air:	N/D
	Carbon Dioxide		
Special Fire Fighting Procedures:	Protect against inhalation of combustion	products, self-contained	
	breathing apparatus should be used. Avo	id breathing smoke, fumes,	
	and decomposition products. Product ma		
	form flammable liquids. Burning produces intense heat, dense		
	smoke, and toxic gases such as carbon monoxide, oxides of nitrogen,		
	and traces of cyanide.		
Unusual Hazards:	None Identified	_	

More info about Polyurethane More info about PROP 65



Industrial Plastic Supply 2240 S. Dupont Drive Anaheim, CA 92806 (866-832-9315) www.iplasticsupply.com

V. REACTIVITY DATA

Stability:	Stable at ambient temperatures and pressures	
Incompatibility:	None identified	
Decomposition Products:	Oxides of carbon, water and smoke under burning conditions.	
	Other combustion products are hydrogen cyanide, aromatic and	
	Aliphatic hydrocarbons.	

VI. SPECIAL PROTECTION INFORMATION

Engineering Controls:	Ventilation: Localize Exhaust – As required to reduce dust or vapors	
	below OSHA limits	
Personal Protection Equipment:	Grinding: Wear a dusk mask	
	Hot Wire Cutting: Use an air purifying respirator with an organic	
	cartridge if local ventilation is inadequate.	
	Protective gloves: None required	
	Eye Protection: Safety glasses with side shields or goggles are	
	recommended during cutting, grinding, or machining operations.	

VII. STORAGE, SPILLS, AND DISPOSAL INFORMATION

Storage:	Store Away from sources of direct heat	
Spills:	N/A	
Disposal:	In accordance with any applicable local, state, or federal regulation regarding disposal of polymer waste.	
Environmental Information:	Environmental effects have not been determined.	

VIII. **HEALTH RELATED DATA**

Specific Hazard (s):	Health Hazards (Acute and Chronic) Acute – None known from		
	solid articles. Vapors from hot wire cutting can be irritating and		
	result in coughing. The vapors may contain trace amounts of toluene		
	diisocyanate (TDI) or diphenylmethane diisocyanate (MDI).		
	Chronic – Animal studies indicate that chronic inhalation or		
	overexposure to dusts may cause inflammation of the lungs, fibrosis,		
	and airway obstruction.		
Primary Route (s) of Entry:	Inhalation : Yes, primary route Skin : No		
	Ingestion : No toxic effects		
	Inhalation of dust during grinding and machining, or inhalation of		
	vapors during hot wire cutting.		
First Aid Procedures:	Flush eyes with water if dust from grinding causes irritation		
Toxicology Information:	There is no toxicology information available for this product.		
	However, as with most high molecular weight polymers, this		
	material is considered inert.		

N/A = NOT Applicable

ND = **Not Determined**

Revision Date: 10-31-03

* European Economic Community

Date Issued: 1-1-86

More info about **PROP 65**



Industrial Plastic Supply 2240 S. Dupont Drive Anaheim, CA 92806 (866-832-9315) www.iplasticsupply.com

More info about

Polyurethane